

EXPLORER 710

High-Speed, Ultra-Portable BGAN Terminal

COBHAM

April 2013 Preliminary Data Sheet

The most important thing we build is trust

The next step change

The new EXPLORER 710 announced in April 2013 provides on-demand streaming rates at 650 kbps out of the box. As the world's smallest Class 1 BGAN terminal and the first to take advantage of Inmarsat's new streaming service (High Data Rate), the EXPLORER 710 will deliver high-speed, ultra-portable satellite streaming for broadcasting and other IP-based industry applications.

The EXPLORER 710 includes several advanced new features, including plug and play bonding - simply connect two EXPLORER 710's and double the throughput. A low-end VSAT capability in a portable BGAN form factor.

EXPLORER 710 will be available in September 2013.



EXPLORER 710

High-Speed, Ultra-Portable BGAN Terminal

Raising the BGAN bar

In fall 2013 Cobham SATCOM will launch the all-new EXPLORER 710. An ultra-portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest Class 1 BGAN terminal positioned to support broadcasters in enhancing the quality of mobile outside broadcasting.



Specifications

Dimensions

Total H / W / D:	332 / 279 / 54 mm 13.07 / 10.98 / 2.13 inches
------------------	--

Total weight:

	3.2 kg / 7 lbs (incl. battery)
Antenna:	1.7 kg (tbc)
Transceiver:	1.5 kg (tbc)

Global Services

Voice:	4 kbps AMBE+2
Premium voice:	3.1 kHz audio, 64 kbps
Standard IP:	Up to 492 kbps
Streaming IP:	32, 64, 128 kbps (256 kbps & BGAN X-Stream - tbc)
High Data Rate Streaming:	+ 650 kbps + 325 kbps (Half-channel HDR)
ISDN:	UDI 64 kbps / RDI 56 kbps
SMS:	Supported

Inmarsat frequencies:	1518.0 - 1525.0 MHz (Rx) (EMEA) 1525.0 - 1559.0 MHz (Rx) 1626.5 - 1660.5 MHz (Tx) 1668.0 - 1675.0 MHz (Tx) (EMEA)
------------------------------	--

EIRP:	20dBW ±1dB
--------------	------------

User Interface: PMOLED Display, 5 navigation keys,
Audio and LCD pointing aids and LED
indicator, Compass

Languages: UK, FR, DE, ES, RU and CN

Approvals: Inmarsat Class 1 Type Approval at launch
CE & FCC at launch. Other approvals TBC

Fastest ever BGAN

The first and only BGAN terminal to support the new on-demand streaming service from Inmarsat. With speeds at 650 kbps the EXPLORER 710 sets a new standard for mobile video newsgathering. The High Data Rate service will be launched by Inmarsat in Fall 2013.

Double the speed with plug and play bonding - simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Interfaces

1 x Analogue RJ-11 phone/fax interfaces

2 x LAN interface

Connector type:	RJ-45
Power over Ethernet:	PoE Cl. 2 on one RJ-45 interface
Data rate:	10/100 Mbps
Max. cable length:	100m / 328ft (Cat5 UTP)

1 x USB host interface

Version:	2.0 (host)
Connector type:	A plug
Charging:	Up to 2A

1 x ISDN interface

Connector type:	RJ-45
Max. units per port:	8, max. total power supplied 1W

1 x Transceiver / Antenna interface

Connector type:	TNC-TNC
Max. cable length:	100m / 328ft, single coax
Max. cable loss:	1.4 / 20dB @ 1.5GHz

1 x BGAN SIM-Card slots

WLAN Access Point

Standard:	IEEE 802.11 b/g
Frequencies:	2400.0-2485.0 MHz
Max. coverage outdoor:	100m / 328ft

Environmental conditions

Temperature

Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F

Battery storage temperature

1 month:	-20°C to +60°C / -4°F to +140°F
3 months:	-20°C to +45°C / -4°F to +113°F
1 year:	-20°C to +20°C / -4°F to +68°F

Water and dust: Transceiver: IP52 / Antenna: IP66

COBHAM

Smart and Easy

The new flagship in the EXPLORER series introduces Smart Phones to the world of BGAN, enabling users to connect their own devices for voice calling and connectivity.

Other features includes a USB host interface, hot-swappable batteries, an easy-to-use LED display and multiple interfaces to support a wide range of applications.

Power

DC input range: 10-32VDC

Power consumption

Intelligent Power Management 65W (max.)

AC/DC power supply

Input:	100-240VAC, 47-63Hz, 65W
Output:	19VDC
Connector type:	2.5 / 5.5 mm power jack

Battery:

	Lithium ion, rechargeable
Stand-by time:	36h, 25°C / 77°F
Transmit time, max.:	2h30m @ 144 kbps (25°C / 77°F) 1h30m @ 492 kbps
Receive time, max.:	3h30m @ 492 kbps
Recharge time:	To be confirmed
Charge temperature:	0°C to +45°C / 32°F to +113°F

Other features

Support for BGAN bonding
Built-in SIP server
Embedded webserver
Advanced Router with admin control
Wireless Access Point
Remote Activation and Remote Management
Battery hot-swap and Intelligent Power Management
Solar Panel powering

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide, CD with manuals.

Important dates

Announcement: April 2013

General Availability: September 2013



Note: All specifications are preliminary and are subject to change without notice.



SatellitePhoneStore.com
Sales@SatellitePhoneStore.com
+1.877.943.6383

2100 19th Street
Sarasota, Florida 34234 USA

Alaska Office
1231 West Northern Lights Blvd, Suite 202
Anchorage, Alaska 99503 USA
+1.907.272.7368

California Office
2830 Shelter Island Dr.
San Diego, CA 92106
+1.619.399.3800